
51453 RAM 1500,2500,3500

ELECTRIC BRAKE CONTROL ADAPTER HARNESS ARNÉS DEL ADAPTADOR DEL CONTROL DEL FRENO ELÉCTRICO. FAISCEAU D'ADAPTATEUR DE COMMANDE DE FREIN ÉLECTRIQUE



MUST READ FIRST!

All steps must be followed to ensure correct function of the T-Connector. To verify proper installation once installed, test by connecting a test light or properly wired trailer.

IDEBE LEERSE PRIMERO!

Debe seguirse todos los pasos para asegurar el correcto funcionamiento del Conector-T. Para verificar la correcta instalación, pruebe conectando una luz de prueba o un remolque debidamente cableado.

À LIRE D'ABORD!

Pour assurer le bon fonctionnement du T-Connector, il faut suivre toutes les étapes. Pour vérifier que l'installation a été bien effectuée, branchez un feu de test ou une remorque correctement filetée.

10/18/2013

English

1. Open the driver's side door and remove the two screws from the lower dash panel (A). Remove the lower dash panel by pulling outwards on it.

2. Locate the vehicle's brake control connectors under the dash above the gas pedal. There will be two different size connectors wrapped in foam and taped to other wiring (B).

3. Remove tape and protective cover from both connectors taking care not to damage the locking tabs. The vehicle's connector will be similar in size and color to the one on the brake control harness.

4. Locate the vehicle's 4-Pin connector. Insert the 4-Pin brake control harness connector into vehicle's connector (C). Make sure the connectors are fully inserted with locking tabs in place (E).

5. Locate the vehicle's 2-Pin connector. Insert the 2-Pin brake control harness connector into vehicle's connector (D). Make sure the connectors are fully inserted with locking tabs in place (E).

6. Route brake control harness to brake controller and insert into mating plug (F).

7. Complete the installation using the brake controller instructions. Mount the unit as directed and perform test procedures as instructed in the brake control's user manual.

INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

